

Package ‘xtbhst’

April 27, 2026

Title Bootstrap Slope Heterogeneity Test for Panel Data

Version 1.0.2

Description Implements the bootstrap slope heterogeneity test for panel data based on Blomquist and Westerlund (2015) <[doi:10.1007/s00181-015-0978-z](https://doi.org/10.1007/s00181-015-0978-z)>. Tests the null hypothesis that slope coefficients are homogeneous across cross-sectional units. Provides both standard and adjusted Delta statistics with bootstrap p-values. Supports partialling out of control variables and cross-sectional averages for dealing with cross-sectional dependence.

License GPL-3

URL <https://github.com/muhammedalkhalaf/xtbhst>

BugReports <https://github.com/muhammedalkhalaf/xtbhst/issues>

Encoding UTF-8

RoxygenNote 7.3.3

Depends R (>= 3.5.0)

Imports stats, graphics, grDevices

Suggests testthat (>= 3.0.0), plm

Config/testthat/edition 3

NeedsCompilation no

Author Muhammad Alkhalaf [aut, cre, cph] (ORCID:
<<https://orcid.org/0009-0002-2677-9246>>),
Tore Bersvendson [ctb]

Maintainer Muhammad Alkhalaf <muhammedalkhalaf@gmail.com>

Repository CRAN

Date/Publication 2026-04-27 18:30:02 UTC

Contents

plot.xtbhst	2
print.xtbhst	2
summary.xtbhst	3
xtbhst	3

Index**6**

plot.xtbhst	<i>Plot method for xtbhst objects</i>
-------------	---------------------------------------

Description

Produces diagnostic plots for the bootstrap slope heterogeneity test.

Usage

```
## S3 method for class 'xtbhst'
plot(x, which = c(1L, 2L), ask = NULL, ...)
```

Arguments

x	An object of class "xtbhst".
which	Integer vector specifying which plots to produce: 1 = Bootstrap distribution of Delta, 2 = Bootstrap distribution of adjusted Delta, 3+ = Individual coefficient distributions. Default is c(1, 2).
ask	Logical. If TRUE, prompt before each plot (default: TRUE if multiple plots and interactive session).
...	Additional arguments passed to plotting functions.

Value

Invisibly returns NULL.

print.xtbhst	<i>Print method for xtbhst objects</i>
--------------	--

Description

Print method for xtbhst objects

Usage

```
## S3 method for class 'xtbhst'
print(x, digits = 4L, ...)
```

Arguments

x	An object of class "xtbhst".
digits	Number of digits to display (default: 4).
...	Additional arguments (ignored).

Value

Invisibly returns the input object.

summary.xtbhst	<i>Summary method for xtbhst objects</i>
----------------	--

Description

Summary method for xtbhst objects

Usage

```
## S3 method for class 'xtbhst'
summary(object, digits = 4L, ...)
```

Arguments

object	An object of class "xtbhst".
digits	Number of digits to display (default: 4).
...	Additional arguments (ignored).

Value

Invisibly returns a list with summary statistics.

xtbhst	<i>Bootstrap Slope Heterogeneity Test for Panel Data</i>
--------	--

Description

Implements the bootstrap slope heterogeneity test based on Blomquist and Westerlund (2015). Tests the null hypothesis that slope coefficients are homogeneous across cross-sectional units.

Usage

```
xtbhst(
  formula,
  data,
  id,
  time,
  reps = 999L,
  blocklength = NULL,
  partial = NULL,
  csa = NULL,
  csa_lags = 0L,
  constant = TRUE,
  seed = NULL
)
```

Arguments

formula	A formula of the form $y \sim x_1 + x_2 + \dots$ specifying the dependent variable and regressors.
data	A data frame containing the panel data.
id	A character string specifying the name of the cross-sectional identifier variable.
time	A character string specifying the name of the time variable.
reps	Integer. Number of bootstrap replications (default: 999).
blocklength	Integer. Block length for the block bootstrap. If NULL (default), set automatically to $\text{floor}(2 * T^{(1/3)})$ where T is the number of time periods.
partial	Optional formula specifying variables to be partialled out. For example, $\sim z_1 + z_2$.
csa	Optional formula specifying variables for which cross-sectional averages should be computed and included. Used to handle cross-sectional dependence following Pesaran (2006).
csa_lags	Integer. Number of lags of the cross-sectional averages to include (default: 0).
constant	Logical. If TRUE (default), include a constant (partialled out).
seed	Optional integer seed for reproducibility.

Details

The test is based on the following Delta statistic:

$$\Delta = \sqrt{N} \frac{\tilde{S}/N - K}{\sqrt{2K}}$$

where \tilde{S} is a weighted sum of squared deviations of individual slope estimates from the weighted pooled estimate.

The adjusted Delta statistic corrects for small sample bias:

$$\Delta_{adj} = \sqrt{N} \frac{\tilde{S}/N - K}{\sqrt{V}}$$

where $V = 2K(T - K - K_{partial} - 1)/(T - K_{partial} + 1)$.

Under the null hypothesis of slope homogeneity, both statistics are asymptotically standard normal. The bootstrap procedure provides finite-sample p-values.

The function requires a strongly balanced panel (all units observed for all time periods).

Value

An object of class "xtbhst" containing:

delta The Delta test statistic.

delta_adj The adjusted Delta test statistic.

pval Bootstrap p-value for the Delta statistic.

pval_adj Bootstrap p-value for the adjusted Delta statistic.
blocklength The block length used in the bootstrap.
reps Number of bootstrap replications.
N Number of cross-sectional units.
T Number of time periods.
K Number of regressors.
beta_i Matrix of individual slope estimates (N x K).
beta_fe Vector of weighted fixed effects (pooled) estimates.
delta_stars Vector of bootstrap Delta statistics.
delta_adj_stars Vector of bootstrap adjusted Delta statistics.
call The matched call.

References

Blomquist, J., & Westerlund, J. (2015). Panel bootstrap tests of slope homogeneity. *Empirical Economics*, 48(1), 1191-1204. doi:10.1007/s001810150978z

Pesaran, M. H. (2006). Estimation and inference in large heterogeneous panels with a multifactor error structure. *Econometrica*, 74(4), 967-1012. doi:10.1111/j.14680262.2006.00692.x

Examples

```
# Generate example panel data
set.seed(123)
N <- 20 # cross-sectional units
T_periods <- 30 # time periods

# Homogeneous slopes (H0 is true)
data_hom <- data.frame(
  id = rep(1:N, each = T_periods),
  time = rep(1:T_periods, N),
  x = rnorm(N * T_periods)
)
data_hom$y <- 1 + 0.5 * data_hom$x + rnorm(N * T_periods)

# Test for slope heterogeneity
result <- xtbhst(y ~ x, data = data_hom, id = "id", time = "time",
               reps = 199, seed = 42)

print(result)
summary(result)
```

Index

`plot.xtbhst`, 2

`print.xtbhst`, 2

`summary.xtbhst`, 3

`xtbhst`, 3